



VERLACTM AS

HIGH PERFORMANCE

SINGLE PACK FLOOR COATING/METALLIC SUBSTRATE

BENEFITS

- < Slip resistant in dry conditions
- < Good chemical and abrasion resistant
- < Can be used most successful areas where personnel need fraction to more objects on smooth surfaces (eg. Powder floated concrete), outdoor area stadium running court, marking etc... .
- < Single pack
- < Easily applied by brush or roller
- < Non-toxic
- < Good bonding with metallic surface and galvanized steel
- < Available in range of colors

PRODUCT

A low cost colored medium duty resin based single pack floor coating, with a matt finish. **VERLAC AS** has good wearing ability with the distinct advantage of very fast drying. No Mixing is needed there is no waste surplus material can be stored.

APPLICATION

Surface should be sound and leveled. Blow holes and surface defects can be made good with FAIRSCREED VF or FAIRSCREED PF Putty to facilitate the application of uniform continuous coatings.

Application : Stir the contents of the bucket and apply by brush or roller. After drying 1st coat applied 2nd coat.

Can be used as self primer product OR special primer clear or colored can be used .

PACKING & COVERAGE

1ltr. **VERLAC AS** will cover 8-10m².at 50-75microns basically but more thickness could be applied according to technical requirements and substrate status , and this will result less yield than mentioned .

HEALTH & SAFETY

Wear gloves & goggles wash off splashes immediately with soap and water.

TECHNICAL SERVICES

While new advances and changes will take place but one thing will never change is quality and meeting special needs of our customers. Our technical personnel & experts are available to provide additional information and technical assistance. We are eager to work with you in development of new product and resolve your problems.

QUALITY ASSURANCE

HAMCO SARL manufactures entire range of construction chemicals Protective coatings ,wood coatings ,decorative paints ,water proofing systems and concrete repair .

TYPICAL PROPERTIES :

SOLID	:60%+/-2%
COLORE	:WHITE OR COLORED DIFFERENT-OR CLEAR
SOLVENT	:XYLENE
KG/LIT	:1.3+/-5%
YIELD	:50-75microns 8/10m² or according to technical request .

The information given in this data sheet is based on both the current development work and many years of field experience. Whilst every effort is made to ensure that the information is reliable, we cannot accept the responsibility for any work carried out with our materials as we have no control over methods of application, site conditions etc. In view of the continuing research and development being undertaken in our laboratories we advise customers in their-own interest to ensure that this data sheet has not been supersede by more up-to-date publication. All products are sold subjected to our standard conditions of sale which are available an request. Field services, where provided, does not constitute supervisory responsibility. For additional information, please contact our local HAMCO SARL -VERLAC-representative.

©Registered Trade Mark