



DECORATIVE COATINGS

TECHNICAL DATA SHEET

VINOTEX RM

ROLL TEXTURE FAÇADE PAINT

A GOOD QUALITY TEXTURED EMULSION PAINT MANUFACTURED FROM GOOD QUALITY AND CAREFULLY SELECTED RAW MATERIALS OFFERING PROTECTION FOR OUTDOOR FAÇADE BUILDING SURFACES, PROVIDING CONSISTENCE COVERING POWER AT A GOOD INVESTMENT COST IF COMPARED TO QUALITY , IDEALLY SUITED FOR CONTRACT PAINTING AND AVAILABLE IN A WIDE RANGE OF TEXTURE AND COLORS TO COVER ANY DECORATIVE NEED.

Properties & Uses

- Wide color range
- Suitable for new concrete coating, cement, brick, stone and many other surfaces including soft board and hardboard, asbestos sheets.
- Exceptional ease of application which dries and gives hard sandy touch effect.
- Good hiding power, good drying
- good color retention
- Very good alkali resistant
- Can be applied over waterproofing primer

Application

Can be applied using Roller brush and hopper spray gun or volumetric spray unit and than applied with roller brush to give the texture effect ,Thinning if necessary use water in limited quantity -use VINOSEAL/c or 100 As primer.

TECHNICAL SPECS

BINDER VINOTEX RM :Acrylic for outdoor use

Product type :Water base

Texture grain : medium

Specific gravity :1.75 kg/lit +/-3%

Solid /volume :>65%

One pail/25kg theoretically can cover about 10 to 20m² depending on the surface situation And grain size needed and thickness .

Application Techniques

hopper gun applicable, use appropriate water needed quantity and enough pressure for better atomization nozzle 4to 6 mm

Volumetric unit with nozzle of 6 or 8mm Graco Tough Tek P30 -Wagner PC 5 or equivalent

Preparation

Prepare the surface well, surface should be clean from all dirt, grease/oil or any other contaminant or flakes, dry well no moisture for better adhesion

Apply as a primer VINOSEAL C/OR 100 first coat than keep overnight than apply VINOTEX RM.

Health & Safety

Provided that reasonable standards are maintained & safe working practices followed, there are no hazards in the handling of Vinolac Emulsion paint following the basic safety measures as good ventilation at application and drying, keep away of reach of childrenetc

Drying time @25C about 1 to 2 hours under normal conditions .

complete drying @25C 24hrs



Haber Bldg, Rwees Street, Fanar -Lebanon Tel/fax : 00961 1 696320
Commercial branche Hazmieh- Lebanon Tel/fax : 009615454292

www.hamcolb.com Email : infotec@hamcolb.com

NOTE: We warranty only the quality of our product and this data sheet is based on results obtained from experience and lab tests. We reserve the right to change data without prior notice. For surface preparation, safety details refer specifier and safety data. The company is not responsible of any caused damage to property or people due to unprofessional use of product .do not put in drain sewage.



Haber Bldg, Rwees Street, Fanar –Lebanon Tel/fax : 00961 1 696320
Commercial branche Hazmieh- Lebanon Tel/fax : 009615454292
www.hamcolb.com Email : infotec@hamcolb.com